



Kaushik Bitumen Pressure Distributor







SALIENT FEATURES

- Fully Insulated Tank with High Efficiency Heating System
- Air Cooled Diesel Engine & Positive Displacement Gear Pump
- Designed To Stuff Standard Truck Chassis
- Safe & Easy In Operation
- · Hand Spray System
- Unique Pressure Cleaning System
- Totally Factory Tested, Arrives Ready To Launch

TEMPERATURE INDICATORS

0 – 300 C (Analog) Scale Located On The Tank.

Digital Temperature Indicator with speed indicator

SPRAY BAR

Standard Width: 2.4 M.

Adjustable Extension Bar For Spraying Width up to 4.2 M.

Nozzle Distance: 225mm Nozzle c/c.

Pneumatically Operated Nozzles For Spray Bar Controlling.

With Hand Torch Burner

BITUMEN PUMP

2" x 2", 350 Lpm, Positive Displacement Gear Pump.

AIR COMPRESSOR


Twin Cylindered, 3HP, 360 LPM Capacity With Working Pressure Of 9 Kg/cm²

DRIVING UNIT

Powered By A 25HP Air Cooled Diesel Engine

BITUMEN SPRAYING PRESSURE

0 – 6 Kg/cm², Pressurized Bitumen Spraying.



TECHNICAL SPECIFICATIONS*

MODEL	KEW - 4000	KEW-6000	KEW - 10000
Tank Details			
Length – L	2400 mm	3000 mm	4400 mm
Width-W	1800 mm	1860 mm	2208 mm
Hight – H	1500 mm	1810 mm	1810 mm
Capacity	4000 ltrs.	6000 ltrs.	10000 ltrs.
Man Hole	600 mm	600 mm	600 mm - 2 Nos.
Insulation	50 mm	50 mm	50 mm
Shape	Ellipse Shape	Ellipse Shape	Ellipse Shape
Burner			
Туре	Compressed Air	Compressed Air	Compressed Air
Burner Fuel Tank	50 ltrs.	50 ltrs.	75 ltrs.
Engine Fuel Tank	20 ltrs.	20 ltrs.	20 ltrs.
Service Tank	20 ltrs.	20 ltrs.	20 ltrs.
Recommended Chassis			
Wheel Base – WB	3760 mm	4470 mm	5030 mm
Clear Chassis Length - CL	4850 mm	5750 mm	7000 mm

st With KEW's policy of constant up gradation of products, specifications are subject to change without prior notice.







ADDRESS: Plot 520, Road No. 14 Kathwada GIDC, Odhav-kathwada Road,

Ahmedabad - 382430, Gujarat, India.

PHONE: +91 79 22901989, 22902714, 29701311

FAX: +91 79 22902815





www.KaushikEngineeringWorks.com